



| Size (Inches) | 2" | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" |
|---------------|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| S(RF)[mm] | 203 | 241 | 292 | 406 | 495 | 622 | 699 | 788 | 914 | 978 | 978 | 1295 |
| S [mm] | 203 | 241 | 292 | 406 | 495 | 622 | 699 | 788 | 914 | 978 | 978 | 1295 |
| H [mm] | 140 | 210 | 270 | 360 | 460 | 570 | 700 | 770 | 870 | 975 | 1095 | 1300 |
| H1[mm] | 190 | 260 | 340 | 400 | 580 | 660 | 800 | 1200 | 1400 | 1530 | 1750 | 2040 |
| Weight [kg] | 14 | 26 | 40 | 68 | 140 | 190 | 270 | 350 | 640 | 700 | 895 | 1370 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: 3/4" NPT

| Size (Inches) | 2" | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" |
|---------------|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|
| S(RF)[mm] | 267 | 318 | 356 | 445 | 559 | 622 | 711 | 838 | 864 | 978 | 1016 | 1346 |
| S [mm] | 267 | 318 | 356 | 445 | 559 | 622 | 711 | 838 | 864 | 978 | 1016 | 1346 |
| H [mm] | 175 | 240 | 330 | 380 | 500 | 625 | 740 | 805 | 920 | 1025 | 1140 | 1360 |
| H1[mm] | 250 | 275 | 360 | 470 | 575 | 920 | 1100 | 1200 | 1360 | 1350 | 1700 | 2050 |
| Weight [kg] | 20 | 45 | 65 | 105 | 180 | 254 | 430 | 670 | 750 | 863 | 1125 | 1625 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: ¾" NPT

| Size (Inches) | 2" | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" |
|---------------|-----|-----|-----|-----|-----|-----|------|------|------|
| S(RTJ)[mm] | 295 | 259 | 435 | 562 | 663 | 790 | 841 | 892 | 994 |
| S(RF)[mm] | 292 | 356 | 432 | 559 | 660 | 787 | 838 | 889 | 991 |
| S [mm] | 292 | 356 | 432 | 559 | 660 | 787 | 838 | 889 | 991 |
| H[mm] | 193 | 260 | 310 | 400 | 500 | 600 | 720 | 865 | 991 |
| H1[mm] | 270 | 320 | 400 | 530 | 650 | 790 | 1200 | 1420 | 1520 |
| Weight [kg] | 35 | 60 | 95 | 230 | 400 | 590 | 700 | 770 | 1140 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: ¾" NPT

| Size (Inches) | 2" | 3" | 4" | 6" | 8" | 10" | 12" |
|--------------------|-----|-----|-----|-----|-----|------|------|
| <i>S(RTJ)[mm]</i> | 371 | 384 | 460 | 613 | 740 | 841 | 968 |
| <i>S(RF)[mm]</i> | 368 | 381 | 457 | 610 | 737 | 838 | 965 |
| <i>S [mm]</i> | 368 | 381 | 457 | 610 | 737 | 838 | 965 |
| <i>H[mm]</i> | 250 | 295 | 375 | 555 | 665 | 650 | 650 |
| <i>H1[mm]</i> | 400 | 320 | 435 | 630 | 780 | 890 | 976 |
| <i>Weight [kg]</i> | 55 | 83 | 155 | 261 | 600 | 1494 | 1750 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: ¾" NPT



CAST STEEL “ Y “ D-KTC TYPE STRAINERS
C1500 WCB / C1500 CF8M
Pressure Seal

| Size (Inches) | 10" | 12" | 14" | 16" |
|---------------|------|------|------|------|
| S(RTJ)[mm] | 1000 | 1146 | 1276 | 1407 |
| S [mm] | 864 | 991 | 1067 | 1194 |
| H[mm] | 700 | 800 | 970 | 1150 |
| H1[mm] | 1100 | 1300 | 1500 | 1700 |
| Weight [kg] | 1200 | 1500 | 2320 | 2750 |

STANDARD PERFORATIONS: 1.5 mm
 SPECIAL PERFORATIONS ON REQUEST
 DRAIN PLUG: ¾" NPT



CAST STEEL “ Y “ D-KTC TYPE STRAINERS
C1500 WCB / C1500 CF8M

| Size (Inches) | 2" | 3" | 4" | 6" | 8" |
|---------------|-----|-----|-----|-------|-----|
| S(RTJ)[mm] | 371 | 473 | 549 | 711.5 | 842 |
| S [mm] | 368 | 470 | 546 | 705 | 832 |
| H[mm] | 250 | 325 | 375 | 480 | 620 |
| H1[mm] | 400 | 540 | 600 | 750 | 900 |
| Weight [kg] | 60 | 100 | 160 | 400 | 600 |

STANDARD PERFORATIONS: 1.5 mm
 SPECIAL PERFORATIONS ON REQUEST
 DRAIN PLUG: ¾" NPT

| Size (Inches) | 1/2" | 3/4" | 1" | 1.1/2" | 2" | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" |
|------------------|------|------|-----|--------|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| S(RF)[m m] | 108 | 117 | 127 | 165 | 203 | 241 | 292 | 406 | 495 | 622 | 699 | 788 | 914 | 978 | 978 | 1295 |
| S [mm] | 108 | 117 | 127 | 165 | 203 | 241 | 292 | 406 | 495 | 622 | 699 | 788 | 914 | 978 | 978 | 1295 |
| H [mm] | 67 | 73 | 87 | 120 | 140 | 210 | 270 | 360 | 460 | 570 | 700 | 770 | 870 | 975 | 1095 | 1300 |
| H1[mm] | 180 | 210 | 240 | 270 | 190 | 260 | 340 | 400 | 580 | 660 | 800 | 1200 | 1400 | 1530 | 1750 | 2040 |
| Weight [kg] | 6 | 9 | 11 | 20 | 14 | 26 | 40 | 68 | 140 | 190 | 270 | 350 | 640 | 700 | 895 | 1370 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: 3/4" NPT

| Size (Inches) | 1/2" | 3/4" | 1" | 1.1/2" | 2" | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" |
|------------------------|------|------|-----|--------|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|
| <i>S(RF)[m m]</i> | 152 | 178 | 203 | 229 | 267 | 318 | 356 | 445 | 559 | 622 | 711 | 838 | 864 | 978 | 1016 | 1346 |
| <i>S [mm]</i> | 152 | 178 | 203 | 229 | 267 | 318 | 356 | 445 | 559 | 622 | 711 | 838 | 864 | 978 | 1016 | 1346 |
| <i>H [mm]</i> | 70 | 80 | 115 | 128 | 175 | 240 | 330 | 380 | 500 | 625 | 740 | 805 | 920 | 1025 | 1140 | 1360 |
| <i>H1[mm]</i> | 150 | 170 | 240 | 260 | 250 | 275 | 360 | 470 | 575 | 920 | 1100 | 1200 | 1360 | 1350 | 1700 | 2050 |
| <i>Weight [kg]</i> | 6 | 9 | 11 | 20 | 20 | 45 | 65 | 105 | 180 | 254 | 430 | 670 | 750 | 863 | 1125 | 1625 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: 3/4" NPT

| Size (Inches) | 1/2" | 3/4" | 1" | 1.1/2" | 2" | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" |
|--------------------|------|------|-----|--------|-----|-----|-----|-----|-----|-----|------|------|------|
| <i>S(RTJ)[mm]</i> | 165 | 191 | 203 | 216 | 295 | 259 | 435 | 562 | 663 | 790 | 841 | 892 | 994 |
| <i>S(RF)[mm]</i> | 165 | 191 | 203 | 216 | 292 | 356 | 432 | 559 | 660 | 787 | 838 | 889 | 991 |
| <i>S [mm]</i> | 165 | 191 | 203 | 216 | 292 | 356 | 432 | 559 | 660 | 787 | 838 | 889 | 991 |
| <i>H [mm]</i> | 120 | 140 | 115 | 170 | 193 | 260 | 310 | 400 | 500 | 600 | 720 | 865 | 991 |
| <i>H1[mm]</i> | 180 | 210 | 240 | 240 | 270 | 320 | 400 | 530 | 650 | 790 | 1200 | 1420 | 1520 |
| <i>Weight [kg]</i> | 6 | 9 | 11 | 11 | 35 | 60 | 95 | 230 | 400 | 590 | 700 | 770 | 1140 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: 3/4" NPT

| Size (Inches) | 2" | 3" | 4" | 6" | 8" | 10" | 12" |
|---------------|-----|-----|-----|-----|-----|------|------|
| S(RTJ)[mm] | 371 | 384 | 460 | 613 | 740 | 841 | 968 |
| S(RF)[mm] | 368 | 381 | 457 | 610 | 737 | 838 | 965 |
| S [mm] | 368 | 381 | 457 | 610 | 737 | 838 | 965 |
| H [mm] | 250 | 295 | 375 | 555 | 665 | 650 | 650 |
| H1[mm] | 400 | 320 | 435 | 630 | 780 | 890 | 976 |
| Weight [kg] | 55 | 83 | 155 | 261 | 600 | 1494 | 1750 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: ¾" NPT

| <i>Size (Inches)</i> | <i>10"</i> | <i>12"</i> | <i>14"</i> | <i>16"</i> |
|----------------------|------------|------------|------------|------------|
| <i>S(RTJ)[mm]</i> | 1000 | 1146 | 1276 | 1407 |
| <i>S(RF)[mm]</i> | 991 | 1130 | 1257 | 1384 |
| <i>S [mm]</i> | 864 | 991 | 1067 | 1194 |
| <i>H [mm]</i> | 700 | 800 | 970 | 1150 |
| <i>H1[mm]</i> | 1100 | 1300 | 1500 | 1700 |
| <i>Weight [kg]</i> | 1200 | 1500 | 2320 | 2750 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: ¾" NPT

| Size (Inches) | 2" | 3" | 4" | 6" | 8" |
|--------------------|-----|-----|-----|-------|-----|
| <i>S(RTJ)[mm]</i> | 371 | 473 | 549 | 711.5 | 842 |
| <i>S(RF)[mm]</i> | 368 | 470 | 546 | 705 | 832 |
| <i>S [mm]</i> | 368 | 470 | 546 | 705 | 832 |
| <i>H [mm]</i> | 250 | 325 | 375 | 480 | 620 |
| <i>H1[mm]</i> | 400 | 540 | 600 | 750 | 900 |
| <i>Weight [kg]</i> | 60 | 100 | 160 | 400 | 600 |

STANDARD PERFORATIONS: 1.5 mm
 SPECIAL PERFORATIONS ON REQUEST
 DRAIN PLUG: ¾" NPT

| <i>Size (Inches)</i> | <i>6"</i> | <i>8"</i> | <i>10"</i> | <i>12"</i> | <i>14"</i> |
|----------------------|-----------|-----------|------------|------------|------------|
| <i>S(RTJ)[mm]</i> | 927 | 1038 | 1292 | 1444 | - |
| <i>S [mm]</i> | 610 | 762 | 914 | 1041 | 1118 |
| <i>H [mm]</i> | 580 | 570 | 750 | 800 | 820 |
| <i>H1[mm]</i> | 820 | 850 | 1100 | 1200 | 1250 |
| <i>Weight [kg]</i> | - | - | - | - | - |

STANDARD PERFORATIONS: 1.5 mm
 SPECIAL PERFORATIONS ON REQUEST
 DRAIN PLUG: ¾" NPT

| <i>Size (Inches)</i> | <i>2”</i> |
|----------------------|-----------|
| <i>S(RTJ)[mm]</i> | 467 |
| <i>S(RF)[mm]</i> | 451 |
| <i>S [mm]</i> | 451 |
| <i>H [mm]</i> | 250 |
| <i>H1[mm]</i> | 400 |
| <i>Weight [kg]</i> | 60 |

STANDARD PERFORATIONS: 1.5 mm
SPECIAL PERFORATIONS ON REQUEST
DRAIN PLUG: ¾” NPT