


POS	DESCRIPTION	MATERIALS	SPARES
1	Ring	SS 304	
2	Perforated plate	ASTM A240 304	
OTHER MATERIALS ON REQUEST			

HOW TO ORDER

i.e. FT2

4" 150# A240 TP304 - PERF. HOLS 3 mm DIA



Conical type temporary strainers are designed for the efficient removal of solids in new pipeline start up service. They are compact and rugged and can be installed either vertically or horizontally. They can be manufactured using any kind of wire mesh or perforated plate, in carbon and stainless steel or exotic alloys. Given dimensions are for reference purpose only. Strainers may be manufactured to any customer's standard. Strainers are designed to be installed between ANSI B16.5 flanges and meet FF, RF and RTJ facings.

SIZE	1½"	2"	3"	4"	6"	8"	10"
D	73	92	127	157	216	270	324
H	60	80	120	150	230	300	350
L	70	70	70	80	100	100	110
C	20	20	20	20	20	20	20
S	3	3	3	3	5	5	5
A	33	48	75	100	150	200	250
B	20	26	44	60	89	118	149

Dimension : D, H, L, C, S, A, B are in millimeters (mm) OTHER SIZES ON REQUEST

SIZE	12"	14"	16"	18"	20"	24"
D	381	412	470	534	584	692
H	400	450	500	550	600	650
L	110	120	130	130	140	150
C	20	20	20	20	20	20
S	5	5	7	7	7	7
A	300	332	383	434	485	587
B	175	194	224	250	285	300

Dimension : D, H, L, C, S , A, B are in millimeters (mm) OTHER SIZES ON REQUEST