



POS	DESCRIPTION	MATERIALS		SPARES
1	Body	ASTM A216 WCB	ASTM A351 CF8(M)	
2	Screen	SS304	SS304/SS316	X
3	Gasket	SW 316/Graphite	SW 316/Graphite	X
4	Cover	ASTM A105N	ASTM A182 F304/316	
5	Bolts	ASTM A193 B7	ASTM A193 B8	
6	Nuts	ASTM A194 2H	ASTM A194 Gr.8	
7/8	Drain/Vent	ASTM A105N		
9* Lifting eyes: on request				
Davit on request				

SIZE (INCHES)	2"	3"	4"	6"	8"
h1 (mm)	110	140	160	180	240
h (mm)	207	265	350	500	650
l (mm)	290	350	420	550	700
Kg	36	47	60	170	290

SIZE (INCHES)	10"	12"	14"	16"
h1 (mm)	315	350	395	430
h (mm)	850	950	1245	800
l (mm)	850	950	1150	1100
Kg	400	535	730	920

D-KTC Pot strainers have been specifically designed to meet all customer requirements including for high pressure applications. Designed and fabricated to ASME B16.34 as standard. Standard features include low pressure drops at high velocities, stainless steel perforated baskets as standard, vents and drains with the possibility to supply davit lifts, quick open closures, DP gauges. We are also able to manufacture against customer requests in all types of materials.

